



MICROCOPY

CHART



AD-A167 406





USAARL Report No. 86-3

A COMPARISON OF SPEECH INTELLIGIBILITY CHARACTERISTICS FOR EARCUPS INTENDED FOR USE IN THE SPH-4 HELMET

By William R. Ngison Ben T. Mozo

SENSORY RESEARCH DIVISION

018

March 1986

FILE COPY

3110

S

March 1980

S

36

Approved for public release, distribution unlimited.

USAARE

Qualified requestors

Qualified requestors may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the US Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Human volunteer use

Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to Army Regulation 70-25 and USAMRDC Regulation 70-25 on Use of Volunteers in Research.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Reviewed:

BRUCE C. LEIBRECHT

LTC. MS

Director, Sensory Research

Division

Released for publication:

J. D. LaMOTHE, Ph.D.

COL, MS

Chairman, Scientific

Review Committee

DEDLEY R. PRICE

Colonel, MC

Commanding

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOS NUMBER
USAARI, Report No. 86-3	6
4. TITLE (and Subtitle)	5. TYPE OF REPORT & PERIOD COVERED
A Comparison of Speech Intelligibility	
Characteristics for Earcups Intended for Use	
in the SPH-4 Helmet	6. PERFORMING ORG. REPORT NUMBER
7 AUTHOR(s)	B. CONTRACT OR GRANT NUMBER(#)
William R. Nelson and Ben T. Mozo	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Sensory Research Division	10. PROGRAM ELEMENT PROJECT, TASK AREA & WORK UNIT HUMBERS
US Army Aeromedical Research Laboratory	62777A 3E162777A878 AC 135
Fort Rucker, AL 36362-5000	VETTIN SETUETTIANTO AC 133
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
US Army Medical Research and Development Command	March 1986
Fort Detrick	13. NUMBER OF PAGES
Frederick, MD 21701-5012	16
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS. (of this report)
	Unclassified
	15a. DECLASSIFICATION DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	
Approved for public release; distribution unlimited	
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, If different from	m Report)
18. SUPPLEMENTARY NOTES	
19 KEY WORDS (Continue on reverse side if necessary and identify by block number)	
Crushable carcups, Speech intelligibility, Noise, S	
Voice communication, MK-1564, Earphones	and the state of t
	Salar Commen
	I would all the Comment
20 ARSTRACT (Continue on severe side if second	
10 ABSTRACT (Continue on reverse side If recessary and identify by block number) Studies at USAARI, have demonstrated significant pro	blome with impact anatostics
in the area of the earcup of the SPH-A aviator halm	


Studies at USAARI, have demonstrated significant problems with impact protection in the area of the earcup of the SPH-4 aviator helmet. Efforts to develop a crushable earcup that will attenuate impact have resulted in development of two candidate earcups. This study compares the speech intelligibility characteristics of the two prototypes to those of the standard SPH-4 earcup and a proposed replacement earcup identified as the MK-1564. The results indicate that both crushable cups will provide speech intelligibility equal to or better than the standard cup.

DD 1 JAM 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

TABLE OF CONTENTS

	PAG	E NO.
List of tables	• • •	2
List of figures	• • •	2
Introduction	• • •	3
Methods and materials	• • •	3
Results and discussion	• • •	7
Conclusion and recommendation	• • •	8
References	• • •	9
Appendixes		
A. List of equipment manufacturers	• • •	10



LIST OF FIGURES

IADLE	NO.	TAGE NO.
1	Conditions used in the evaluation of speech intelligibility	4
2	Octave-band sound pressure level of the simulated UH-60A noise environment	5
3	Percent correct responses for experimental listener's conditions, talker using the SPH-4 microphone	7
4	Tukey's (HSD) multiple comparison of listener's intelligibility using Alpha = .05	8
	LIST OF TABLES	
FIGURE	NO.	PAGE NO.
1 P = ₩	Speech intelligibility test setup	6

INTRODUCTION

The development of the SPH-4 aviator helmet has been recognized as a significant improvement in providing hearing protection and impact absorption for aviation personnel. However, it has been determined that impact protection is compromised significantly in the region of the earcup (Haley et al., 1983). In 1977, USAARL contracted with Simula Incorporated to develop an earcup capable of providing improved impact energy absorption while maintaining sound attenuation equal to or better than that required by the specification for the SPH-4. Sound attenuation results for that effort are reported in USAARL Report No. 84-2. Efforts to identify better and more economical "crushable" earcups have continued. Currently, there are two candidates, one made of aluminum and one made of Cycolac plastic.

Development also has been proceeding on an "improved" conventional earcup for the aviation community, the MK-1564 project. MK-1564 earcups are constructed from hard plastic as are the standard SPH-4 cups, but with different physical dimensions. These earcups were included in this evaluation.

This study focuses on the issue of speech intelligibility (the ability of the aviator to understand oral communication) with the experimental earcups. Recent studies (Mozo and Peters, 1984; and Nelson and Mozo, 1985) have demonstrated the impact of individual components on the overall performance of communications systems in difficult listening situations. The possibility was raised that changing the earcup could degrade the speech communications capability of the SPH-4 helmet. The effects on communications of the three experimental earcups when installed in the SPH-4 aviator helmet were compared to the current SPH-4 earcup.

METHODS AND MATERIALS

Twelve warrant officers with normal hearing were selected as listeners. They were required to have hearing thresholds for each ear no greater than 20 dB at the seven pure tone test frequencies. Listeners were evaluated for acceptability on a standard clinical audiometer (ANSI S3.6-1969). All listeners were used for each of the test conditions of the intelligibility evaluation.

The parameter of speech intelligibility of interest was the ability of the listener to understand speech while in a noise environment. The listeners wore the SPH-4 helmet fitted with the various earcups as described in Table 1. Speech intelligibility of each test condition was measured using lists of 50 phonetically balanced (PB) words. The lists of words used in this experiment are described in ANSI S3.2-1960 (R1971). A different PB word list was used for each of the four experimental conditions. All speaker conditions used words recorded by the same narrator who was seated in a simulated UH-60A helicopter noise environment. An octave band analysis of the noise spectrum is shown in Table 2. The listeners were required to listen to and transcribe the PB words while subjected to the same simulated background noise.

TABLE 1
CONDITIONS USED IN THE EVALUATION OF SPEECH INTELLIGIBILITY

Test condition	Listener condition	Speaker condition
1	Standard SPH-4 cup	SPH-4 microphone
2	Aluminum crushable	SPH-4 microphone
3	Cycolac crushable	SPH-4 microphone
4	MK-1564 prototype	SPH-4 microphone

TABLE 2

OCTAVE-BAND SOUND PRESSURE LEVEL OF THE SIMULATED UH-60A NOISE ENVIRONMENT

Octave-band center frequencies in Hertz

- -	250				16K
	98			83	80

The speech samples used in the experiment were recorded on a Nagra Model IV-SJ* magnetic tape recorder. Each sample list was reproduced and the output recorded on a Bruel and Kjaer (bK) Type 2307* graphic level recorder. From the level recordings, the signal intensity was determined and a 1000 Hertz (Hz) calibration tone was placed at the beginning of each list. Each subject was seated in the simulated noise environment during the test. The speech reception threshold (SRT) for each listening condition was determined to be the signal intensity at which a 50 percent correct response to spondee words was obtained under that test condition. All SRT presentations were made using commercially recorded speech samples. The SRT procedure was used to establish a consistent level of speech signal at the listener's ear for all test subjects. The PB word lists were presented through the test earphones at a level 10 dB above his SRT. This allowed an estimate of speech intelligibility for each condition relative to every other condition at equalized listener levels. The order of presentation of the test conditions was fully crossed.

It must be understood that the intelligibility estimates obtained may not represent scores achievable under conditions different from those tested. Since the test environment was a simulated condition, important variables which influence intelligibility could not be included such as stress, heat, competing tasks, vibration, and others.

The instrumentation used to present the PB words is shown in Figure 1. The Hewlett-Packard (HP) Model 239A* oscillator was used to generate a calibration tone at 1000

^{*}See Appendix A

SPEECH INTELLIGIBILITY TEST SET-UP




FIGURE 1. Speech intelligibility test setup.

Hertz. The HP Digital Multimeter, Model 3465A*, was used to set and monitor intensity. The word lists were reproduced using the same Nagra tape recorder specified. The intensity of the signal presented to the listeners was controlled by an HP Attenuator, Model 4437A*, and an HP Power Amplifier, Model 467A.

RESULTS AND DISCUSSION

The results of the evaluations are shown in Table 3.

TABLE 3

PERCENT CORRECT RESPONSES FOR EXPERIMENTAL LISTENER'S CONDITIONS, TALKER USING THE SPH-4 MICROPHONE

Earcup Test condition	Mean	Standard deviation
Standard SPH-4	55.2	11.10
Aluminum crushable	63.0	6.52
Cycolac crushable	55.7	11.59
MK -1564	47.7	12.03

Table 3 shows a comparison of the average percent correct responses of the listeners for each test condition while the speaker condition was held constant. A repeated measures one-way analysis of variance (ANOVA) as described by Winer (1962) was completed on the listener results. An apriori Type 1 error rate (∞) of .05 was selected. The result of this analysis indicates a significant difference exists between the listener conditions (F(3,44)=4.23, p<.010).

THE PROPERTY OF THE PROPERTY O

A multiple comparison analysis was run using the Honestly Significant Difference (HSD) method described by Tukey (1949). An (OC) of .05 was used with 44 degrees of freedom. The result was a Studentized range equal to 3.79 and an HSD value of 11.54. Table 4 contains a comparison of levels of significant differences between the experimental

earcups. The letters represent factor levels which statistically are different from one another. The lowest level or mean is represented by the letter "A," with subsequent letters representing higher levels or means with statistically significant differences. As shown in Table 4, the standard SPH-4 and the Cycolac earcups are grouped together, but overlap both the aluminum and MK-1564, while the aluminum is significantly better than the MK-1564.

TABLE 4

TUKEY'S (HSD)	MULTIPLE	COMPAR	ISON OF	
LISTENER'S INTELL	IGIBILITY	USING	ALPHA =	.05

	TEST CONDITION				
	Standard SPH-4	Aluminum crushable	Cycolac crushable	MK-1564	
Level of separation	АВ	В	AB	A	

CONCLUSION AND RECOMMENDATION

It may '. concluded from this study that both the aluminum and cycolac crushable earcups provide as good or better speech communication capability as the standard SPH-4 earcup. Further, the MK-1564 provides significantly less communication capability than the aluminum earcup.

It is recommended that a cost analysis and selection process proceed immediately and that a crushable earcup be made standard for all aviator helmets used by DA personnel.

The second of th

REFERENCES

American National Standards Institute. (R 1971).

<u>USA standard method for measurement of monosyllabic word intelligibility.</u>

S3.2-1960.

and acceptance of the property of the property of

- American National Standards Institute. (R 1973).

 American national standard specifications
 for audiometers. S3.6-1969.
- Haley Jr., Joseph L., Shanahan, Dennis F., Reading, Thomas E., and Knapp, Stanley C. 1983. Head impact hazards in helicopter operations and their mitigation through improved helmet design. Impact injury of the head and spine, 18:549-577.
- Mozo, B.T. and Peters, Leslie J. 1984. Effects of chemical protective and oxygen masks on attenuation and intelligibility when worn with the SPH-4 helmet. Fort Rucker, AL: US Army Aeromedical Research Laboratory. USAARL Report No. 84-5.
- Nelson, William R. and Mozo, Ben T. 1985. Effects of XM-40 chemical protective mask on real-ear attenuation and speech intelligibility characteristics of the SPH-4 aviator helmet. Fort Rucker, AL: US Army Aeromedical Research Laboratory. USAARL Report No. 85-2.
- Tukey, J.W. 1949. Comparing individual means in the analysis of variance. Biometrics. 5:99-114.
- Winer, B.J. 1962. Statistical principles in experimental design. New York: McGraw-Hill.

APPENDIX A

LIST OF EQUIPMENT MANUFACTURERS

Bruel and Kjaer Instruments, Inc. 9047-A Gaither Road Gaithersburg, MD 20760

Borg-Warner Corporation 200 S. Michigan Chicago, IL 60604

Hewlett-Packard P.O. Box 28234 450 Interstate North Atlanta, GA 30328

THE PERSON TRANSPORT FOR THE PERSON THE PERSON TO SEE THE PERSON TO SEE THE PERSON THE P

INITIAL DISTRIBUTION

Commander
US Army Natick Research and
Development Center
ATTN: Documents Librarian
Natick, MA 01760

Commander
US Army Research Institute of
Environmental Medicine
Natick, MA 01760

Naval Submarine Medical Research Laboratory Medical Library, Naval Sub Base Box 900 Groton, CT 05340

US Army Avionics Research and Development Activity ATTN: SAVAA-P-TP Fort Monmouth, NJ 07703-5401

Commander/Director
US Army Combat Surveillance and
Target Acquisition Laboratory
ATTN: DELCS-D
Fort Monmouth, NJ 07703-5304

US Army Research and Development Support Activity Fort Monmouth, NJ 07703

Commander 10th Medical Laboratory ATTN: Audiologist APO New York 09180

のからというと、これのないのと、これのないのは、これのないのは、これのないのは、これのないのは、これのないのは、これのないのでは、これのないのは、これのないのは、これのないのは、これのないのは、これの

Chief, Benet Weapons Laboratory LCWSL, USA ARRADCOM ATTN: DRDAR-LCB-TL Watervliet Arsenal, NY 12189

Commander
Naval Air Development Center
Biophysics Lab (ATTN: G. Kydd)
Code 60Bl
Warminster, PA 18974

Commander
Man-Machine Integration System
Code 602
Naval Air Development Center
Warminster, PA 18974

Naval Air Development Center Technical Information Division Technical Support Detachment Warminster, PA 18974

Commander
Naval Air Development Center
ATTN: Code 6021 (Mr. Brindle)
Warminster, PA 18974

Dr. E. Hendler Human Factors Applications, Inc. 295 West Street Road Warminster, PA 18974

Commanding Officer
Naval Medical Research and
Development Command
National Naval Medical Center
Bethesda, MD 20014

Under Secretary of Defense for Research and Engineering ATTN: Military Assistant for Medical and Life Sciences Washington, DC 20301

Director
Army Audiology and Speech Center
Walter Reed Army Medical Center
Washington, DC 20307-5001

COL Franklin H. Top, Jr., MD Walter Reed Army Institute of Research Washington, DC 20307-510C

Commander
US Army Institute of Dental Research
Walter Reed Army Medical Center
Washington, DC 20307-5306

HQ DA (DASG-PSP-0) Washington, DC 20310

Naval Air Systems Command Technical Library Air 950D Rm 278, Jefferson Plaza II Department of the Navy Washington, DC 20361

Naval Research Laboratory Library Code 1433 Washington, DC 20375

Naval Research Laboratory Library Shock & Vibration Information Center Code 5804 Washington, DC 20375

Harry Diamond Laboratories ATTN: Tech Information Branch 2800 Powder Mill Road Adelphi, MD 20783-1197

Director
US Army Human Engineering Laboratory
ATTN: Technical Library
Aberdeen Proving Ground, MD

21005-5001

US Army Materiel Systems
Analysis Agency
ATTN: Reports Processing
Aberdeen Proving Ground, MD
21005-5017

Commander

M. BESSELES SPERFEL SONNOON MOTORING SPREED IN

US Army Test & Evaluation Command ATTN: AMSTE-AD-H Aberdeen Proving Ground, MD 21005-5055

US Army Ordnance Center & School Library Bldg 3071 Aberdeen Proving Ground, MD 21005-5201

Director

US Army Ballistic Research Laboratory 5001 Eisenhower Avenue ATTN: DRXBR-OD-ST Tech Reports Alexandria, VA 22333 Aberdeen Proving Ground, MD 21005-5066

US Army Environmental Hygiene Agency Library Bldg E2100 Aberdeen Proving Ground, MD 21010

Commander

US Army Medical Research Institute of Chemical Defense ATTN: SGRD-UV-AO Aberdeen Proving Ground, MD 21010-5425

Technical Library Chemical Research & Development Center Aberdeen Proving Ground, MD 21010-5423

Commander

US Army Medical Research & Development Command ATTN: SGRD-RMS (Mrs. Madigan) Fort Detrick, Frederick, MD 21701-5012

Commander

US Army Medical Research Institute of Infectious Diseases Fort Detrick, Frederick, MD 21701

Commander

US Army Medical Bioengineering Research & Development Laboratory ATTN: SGRD-UBZ-I Fort Detrick, Frederick, MD 21701

Dr. R. Newburgh Director, Biological Sciences Division Office of Naval Research 600 North Quincy Street Arlington, VA 22217

Defense Technical Information Center Cameron Station Alexandria, VA 22314

Commander
US Army Materiel Command
ATTN: AMCDE-S (CPT Broadwater)
5001 Eisenhower Avenue
Alexandria, VA 22333

US Army Foreign Science and Technology Center ATTN: MTZ 220 7th Street, NE Charlottesville, VA 22901-5396

Commandant US Army Aviation Logistics School ATTN: ATSQ-TDN Fort Eustis, VA 23604 Director, Applied Technology Lab

USARTL-AVSCOM ATTN: Library, Bldg 401 Fort Eustis, VA 23604

US Army Training and Doctrine Command ATTN: ATCD-ZX Fort Monroe, VA 23651

US Army Training and Doctrine Command ATTN: Surgeon Fort Monroe, VA 23651-5000

Structures Laboratory Library USARTL-AVSCOM NASA Langley Research Center Mail Stop 266 Hampton, VA 23665

Aviation Medicine Clinic TMC #22, SAAF Fort Bragg, BC 28305

Naval Aerospace Medical Institute Library Bldg 1953, Code 102 Pensacola, FL 32508

US Air Force Armament Development and Test Center Eglin Air Force Base, FL 32542

Command Surgeon US Central Command MacDill AFB, FL 33608

were not a contrary. Reference (Francisco) and analysis

US Army Missile Command Redstone Scientific Information Center Propulsion Laboratory MS 302-2 ATTN: Documents Section Redstone Arsenal, AL 35898-5241

Air University Library (AUL/LSE) Maxwell AFB, AL 36112

Commander US Army Aeromedical Center Fort Rucker, AL 36362

Commander US Army Aviation Center & Fort Rucker ATTN: ATZQ-CDR Fort Rucker, AL 36362

Directorate of Combat Developments Bldg 507 Fort Rucker, AL 36362

Directorate of Training Development Bldg 502 Fort Rucker, AL 36362

Chief Army Research Institute Field Unit Fort Rucker, AL 36362

Human Engineering Labs Field Unit Fort Rucker, AL 36362

Commander US Army Safety Center Fort Rucker, AL 36362

Commander US Army Aviation Center & Fort Rucker ATTN: ATZQ-T-ATL Fort Rucker, AL 36362

US Army Aircraft Development Test Activity ATTN: STEBG-MP-QA Cairns AAF, Ft Rucker, AL 36362

President US Army Aviation Board Cairns AAF, Ft Rucker, AL 36362

US Army Research & Technology NASA Lewis Research Center Cleveland, OH 44135

AFAMRL/HEX Wright-Patterson AFB, OH 45433

US Air Force Institute of Technology (AFIT/LDEE) Bldg 640, Area B Wright-Patterson AFB, OH 45433

University of Michigan
NASA Center of Excellence
in Man-Systems Research
ATTN: R.G. Snyder, Director
Ann Arbor, MI 48109

Henry L. Taylor Director, Institute of Aviation Univ of Illinois - Willard Airport Savoy, IL 61874

John A. Derlinger, MS, ATP Univ of Illinois - Willard Airport Savoy, IL 61874

Commander

AND RESERVED AND PROPERTY OF THE PROPERTY OF T

US Army Aviation Systems Command ATTN: DRSAV-WS 4300 Goodfellow Blvd St Louis, MO 63120-1798

Project Officer Aviation Life Support Equipment ATTN: AMCPO-ALSE 4300 Goodfellow Blvd St Louis, MO 63120-1798

Commander

US Army Aviation Systems Command ATTN: SGRD-UAX-AL (MAJ Lacy) Bldg 105, 4300 Goodfellow Blvd St Louis, MO 63120

Commander US Army Avia

US Army Aviation Systems Command ATTN: DRSAV-ED 4300 Goodfellow Blvd St Louis, MO 63120

US Army Aviation Systems Command Library & Info Center Branch ATTN: DRSAV-DIL 4300 Goodfellow Blvd St Louis, MO 63120 Commanding Officer Naval Biodynamics Laboratory P.O. Box 24907 New Orleans, LA 70189

Federal Aviation Administration Civil Aeromedical Institute CAMI Library AAC 64D1 P.O. Box 25082 Oklahoma City, OK 73125

US Army Field Artillery School ATTN: Library Snow Hall, Room 14 Fort Sill, OK 73503

Commander

US Army Academy of Health Sciences ATTN: Library Fort Sam Houston, TX 78234

Commander

US Army Health Services Command ATTN: HSOP-SO Fort Sam Houston, TX 78234-6000

Commander

US Army Institute of Surgical Research ATTN: SGRD-USM (Jan Duke) Fort Sam Houston, TX 78234-6200

Director of Professional Services AFMSC/GSP Brooks Air Force Base, TX 78235

US Air Force School
of Aerospace Medicine
Strughold Aeromedical Library
Documents Section, USAFSAM/TSK-4
Brooks Air Force Base, TX 78235

US Army Dugway Proving Ground Technical Library Bldg 5330 Dugway, UT 84022

Dr. Diane Damos Department of Human Factors ISSM, USC Los Angeles, CA 90089-0021

US Army Yuma Proving Ground Technical Library Yuma, AZ 85364

US Army White Sands Missile Range Technical Library Division White Sands Missile Range, NM 88002

US Air Force Flight Test Center Technical Library, Stop 238 Edwards Air Force Base, CA 93523

US Army Aviation Engineering Flight Activity ATTN: SAVTE-M (Tech Lib) Stop 217 Edwards AFB, CA 93523-5000

Commander Code 3431 Naval Weapons Center China Lake, CA 93555

US Army Combat Developments
Experimental Center
Technical Information Center
Bldg 2925
Fort Ord, CA 93941-5000

Aeromechanics Laboratory
US Army Research
& Technical Laboratories
Ames Research Center, M/S 215-1
Moffett Field, CA 94035

Commander
Letterman Army Institute of Research
ATTN: Medical Research Library
Presidio of San Francisco, CA 94129

Sixth US Armv ATTN: SMA Presidio of San Francisco, CA 94129

Director Naval Biosciences Laboratory Naval Supply Center, Bldg 844 Oakland, CA 94625

CONTRACTOR OF THE PROPERTY OF

Co1 G. Stebbing USDAO-AMLO, US Embassy Box 36 FPO New York 09510

Staff Officer, Aerospace Medicine RAF Staff, British Embassy 3100 Massachusetts Avenue, NW Washington, DC 20008

Canadian Society of Aviation Medicine c/o Academy of Medicine, Toronto ATTN: Ms. Carmen King 288 Bloor Street West Toronto, Ontario M55 1V8

Canadian Airline Pilot's Association MAJ J. Soutendam (Retired) 1300 Steeles Avenue East Brampton, Ontario, L6T 1A2

Canadian Forces Medical Liaison Officer Canadian Defence Liaison Staff 2450 Massachusetts Avenue, NW Washington, DC 20008

Commanding Officer 404 Squadron CFB Greenwood Greenwood, Nova Scotia BOP 1NO

Officer Commanding
School of Operational
& Aerospace Medicine
DCIEM, P.O. Box 2000
1133 Sheppard Avenue West
Downsview, Ontario M3M 3B9

National Defence Headquarters 101 Colonel By Drive ATTN: DPM Ottowa, Ontario KlA OK2

Commanding Officer Headquarters, RAAF Base POINT COOK VIC 3029 Australia Canadian Army Liaison Office Bldg 602 Fort Rucker, AL 36362

Netherlands Army Liaison Office Bldg 602 Fort Rucker, AL 36362

German Army Liaison Office Bldg 602 Fort Rucker, AL 36362

British Army Liaison Office Bldg 602 Fort Rucker, AL 36362

French Army Liaison Office Bldg 602 Fort Rucker, AL 36362

6-86